Characteristic features EN 1307

Name of article	**AT Savoy 1100**
Method of production ISO 2424	Tufted
Width ISO 3018	ca. 50x50
Surface structure ISO 2424	Loop
Colourways	Style
Pile material ISO 2424	100% Econyl by Aquafil
Primary backing ISO 2424	PES
Overall weight ISO 8543	ca. 3500 g/m²
Overall thickness ISO 1765	ca. 8,0 mm
Pile service weight	ca. 1150 g/m²
Secondary backing ISO 2424	Welltex® Acoustic
Electrostatic loading ISO 6356	< 2 KV
Surface resistivity ISO 10965 ROT	10^9 Ω
Transparency to heat ISO 8302	0,09 K*m² /W
Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4
Stitch rate ISO 1763	ca. 182.700/m²

EN 14041 | DOP: 1045-123519 | NB: 1658

Health-promoting properties AIR

- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers

HEALTH

Health-promoting ACOUSTIC properties

- High acoustic effectiveness as standard
- Improved impact sound insulation +28dB
  Enhanced room acoustics +0.25α_w
-

Hz	125	250	500	1000	2000	4000
α_s	0,00	0,05	0,15	0,35	0,40	0,50

- Increased employee concentration and motivation through enhanced well-being

Environmental properties

BD06B302
PRODIS-ID | product pass

- Completely recyclable
- 100% recycled yarn
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- Easy cleaning with water only

Made in Europe (production according to EU standard)

Product Information

AT SAVOY - This tile stands out with its mélange loop that creates a tiled appearance. Especially in lighter colors, the tile pattern becomes distinctly visible due to the shadow effects in the tile joints. During initial use, this appearance devolops significantly thanks to daily maintenance with a brush vacuum cleaner. Experience how the tiles gain individual beauty over time.

Installation Instructions

Data status 09.10.2024. Subject to changes due to technical advancements.

OBJECT CARPET GmbH | Marie-Curie-Strasse 3 | D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 | technicalsupport@object-carpet.com

OBJECT CARPET