

OBJECT CARPET

Typical characteristics

Name of article
Method of production ISO 2424
Width ISO 3018
Surface structure ISO 2424
Colourways
Pile material ISO 2424
Primary backing ISO 2424
Secondary backing ISO 2424
Overall weight ISO 8543
Overall thickness ISO 1765
Pile service weight



AT-Scor 550
Needled
approx. 50x50
Needle-felt
Uni
35% PA / 40% PP / 25 % PES
PES
Bitumen Schwerbeschichtung, Bitumen Akustik Plus
approx. 4400 g/m²
approx. 6,5 mm
approx. 550 g/m²

Application

Wearability EN 1307 commercial use heavy (33)
Comfort class EN 1307 LC1

Ecological characteristics

Conformity certificate CE-System 3
DOP 1045-120912
Prodis-ID 225F34D3

Fastness

Light fastness ISO 105-B02 ≥ 5
Water fastness EN ISO 105 E01 ≥ 4
Friction fastness EN ISO 105-X12 ≥ 3-4



Release Date 14.11.2022.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com