



Name of article	AT Silky Seal 1200	Secondary backing ISO 2424	Welltex Circular® Acoustic
Method of production ISO 2424	Tufted	Electrostatic loading ISO 6356	< 2 KV
Width ISO 3018	ca. 50x50	Surface resistivity ISO 10965 ROT	10° Ω
Surface structure ISO 2424	Cut	Transparency to heat ISO 8302	0,09 K*m² /W
Colourways	Uni	Light fastness ISO 105-B02	≥ 5
Pile material ISO 2424	100% PA 6.6	Water fastness EN ISO 105 E01	≥ 4
Primary backing ISO 2424	PES, PET (100% Recycelt)	Friction fastness EN ISO 105-X12	≥ 3-4
Overall weight ISO 8543	ca. 2800 g/m²	Stitch rate ISO 1763	ca. 150.000/m²
Overall thickness ISO 1765	ca. 11,4 mm		
Pile service weight	ca. 1150 g/m²		



EN 14041 | DOP: 1060-OC-3566
CPR: 1658-CPR-3566 | NB: 1658

Health-promoting properties AIR



- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers

HEALTH



70 710 3720-13



Health-promoting ACOUSTIC properties



- High acoustic effectiveness as standard
- Improved impact sound insulation +29dB
- Enhanced room acoustics +0.3α_w

Hz	125	250	500	1000	2000	4000
α _s	0,01	0,05	0,23	0,41	0,50	0,74

- Increased employee concentration and motivation through enhanced well-being



Environmental properties

PRODUS-ID | product pass

- Completely recyclable
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- Easy cleaning with water only



Product Information

AT SILKY SEAL - The carpet presents itself with a velour construction, featuring a shimmering surface of elegant appearance. The choice of color has a decisive impact on the visibility of the tiles as well as the maintenance effort. The lighter the color choice, the more delicate it can be.

Installation Instructions

Great attention is placed on laying the tiles in a harmonious alignment, thus creating a coherent overall image. At the same time, care is taken not to trap the pile - that is, the yarn ends - at the seams, in order to preserve both the aesthetic quality and the lasting functionality of the carpet.



Made in Europe (production according to EU standard)

Data status 19.02.2026. Subject to changes due to technical advancements.