



Name of article	Skill x Chill	Secondary backing ISO 2424	Action back
Method of production ISO 2424	Tufted	Electrostatic loading ISO 6356	<2 KV
Width ISO 3018	ca. 400	Surface resistivity ISO 10965 ROT	10 ⁹ Ω
Surface structure ISO 2424	Loop	Transparency to heat ISO 8302	0,09 K*m ² /W
Colourways	Uni	Light fastness ISO 105-B02	≥ 5
Pile material ISO 2424	100% Econyl by Aquafil	Water fastness EN ISO 105 E01	≥ 4
Primary backing ISO 2424	PP	Friction fastness EN ISO 105-X12	≥ 3-4
Overall weight ISO 8543	ca. 2400 g/m ²	Stitch rate ISO 1763	ca. 216700/m ²
Overall thickness ISO 1765	ca. 8 mm		
Pile service weight	ca. 1170 g/m ²		



EN 14041 | DOP: 1060-OC-6323-C1
CPR: 0809-CPR-19006323-C1 | NB: 1658

Health-promoting properties AIR



- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers

HEALTH



Health-promoting ACOUSTIC properties



- Improved impact sound insulation +27dB
- Enhanced room acoustics +0.2α_w
- | Hz | 125 | 250 | 500 | 1000 | 2000 | 4000 |
|----------------|------|------|------|------|------|------|
| α _s | 0,03 | 0,04 | 0,10 | 0,33 | 0,45 | 0,50 |
- Increased employee concentration and motivation through enhanced well-being
- Acoustically effective



Environmental properties

7AF7FFA3
PRODID | product pass

- 100% recycled yarn
- Recycled primary backing
- Easy cleaning with water only



Product Information

Small crimped loops create a voluminous, structured and at the same time very homogeneous surface appearance. The delayed regeneration behavior of the tufting quality is typical of the product. However, indentations in the fibers recover after a short period of frequent use.

Installation Instructions

An accurate, professional seam cut is made on the back of this shag quality, inside the nap, using a chopping knife. The use of "pile clamps" should be avoided; alternatively, it is recommended that the pile is carefully taped to the side with masking tape, which can be easily removed after insertion.



Made in Europe (production according to EU standard)