

OBJECT CARPET

Typical characteristics

Name of article	 AT-Smoozy 1600
Method of production ISO 2424	Tufted
Width ISO 3018	approx. 50x50
Surface structure ISO 2424	Cut
Colourways	Uni
Pile material ISO 2424	100% PA 6.6
Primary backing ISO 2424	PES
Secondary backing ISO 2424	Welltex® Acoustic
Overall weight ISO 8543	approx. 3200 g/m ²
Overall thickness ISO 1765	approx. 12,0 mm
Pile service weight	approx. 1600 g/m ²

Application

Wearability EN 1307	commercial use general (32)
Comfort class EN 1307	LC5

Ecological characteristics

Conformity certificate	0809-CPR-19006323-C5
DOP	1060 OC 6323-C5
Prodis-ID	366AAE82

Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4



Release Date 21.4.2024.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com