## Characteristic features EN 1307

| | |
|---|---|
| Name of article | **AT Springles Eco 700** |
| Method of production ISO 2424 | Tufted |
| Width ISO 3018 | ca. 50x50 |
| Surface structure ISO 2424 | Loop |
| Colourways | Mix |
| Pile material ISO 2424 | 100% Econyl by Aquafil |
| Primary backing ISO 2424 | PES |
| Overall weight ISO 8543 | ca. 2000 g/m² |
| Overall thickness ISO 1765 | ca. 5,0 mm |
| Pile service weight | ca. 650 g/m² |
| Secondary backing ISO 2424 | Welltex® Acoustic |
| Electrostatic loading ISO 6356 | < 2 KV |
| Surface resistivity ISO 10965 ROT | $10^9$ Ω |
| Transparency to heat ISO 8302 | 0,09 K*m² /W |
| Light fastness ISO 105-B02 | ≥ 6 |
| Water fastness EN ISO 105 E01 | ≥ 5 |
| Friction fastness EN ISO 105-X12 | ≥ 5 |
| Stitch rate ISO 1763 | ca. 158.000/m² |

EN 14041 | DOP: 1060 OC 3497 | NB: 1658

## Health-promoting properties AIR

- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers

HEALTH

## Health-promoting ACOUSTIC properties

- High acoustic effectiveness as standard
- Improved impact sound insulation +25dB
  Enhanced room acoustics +0.2$\alpha_w$
- | Hz | 125 | 250 | 500 | 1000 | 2000 | 4000 |
  |---|---|---|---|---|---|---|
  | $\alpha_s$ | 0,00 | 0,03 | 0,07 | 0,18 | 0,21 | 0,32 |
- Increased employee concentration and motivation through enhanced well-being

## Environmental properties

E0CB9CF1
PRODIS-ID | product pass

- Completely recyclable
- 100% recycled yarn
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- Easy cleaning with water only

Made in Europe (production according to EU standard)

## Product Information

AT SPRINGLES ECO - This tile stands out with its mélange loop that creates a tiled appearance. Especially in lighter colors, the tile pattern becomes distinctly visible due to the shadow effects in the tile joints. During initial use, this appearance devolops significantly thanks to daily maintenance with a brush vacuum cleaner. Experience how the tiles gain individual beauty over time.

## Installation Instructions

Data status 21.04.2024. Subject to changes due to technical advancements.

OBJECT CARPET GmbH | Marie-Curie-Strasse 3 | D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 | technicalsupport@object-carpet.com

OBJECT CARPET