


OBJECT CARPET

Typical characteristics

Name of article	
Method of production ISO 2424	Stream
Width ISO 3018	Getuftet
Surface structure ISO 2424	approx. 400
Pile material ISO 2424	Schlinge
Primary backing ISO 2424	100 % Polyamid Econyl by Aquafil
Secondary backing ISO 2424	PES
Overall weight ISO 8543	Conductive action back
Overall thickness ISO 1765	approx. 2270 g/m ²
Pile service weight	approx. 5.8 mm
	approx. 800 g/m ²

Application

Wearability EN 1307	commercial use heavy (33)
Comfort class EN 1307	LC2

Ecological characteristics

Conformity certificate	1658-CPR3023
DOP	1060 TT 3023
EPD (Environmental Product Declaration)	EPD-GUT-20170017-CCA1-DE
Prodis-ID	BC2DD83B

Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	4
Friction fastness EN ISO 105-X12	≥ 3-4



Release Date 4.5.2022.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com