

OBJECT CARPET

Typical characteristics

Name of article
Method of production ISO 2424
Width ISO 3018
Surface structure ISO 2424
Colourways
Pile material ISO 2424
Primary backing ISO 2424
Secondary backing ISO 2424
Overall weight ISO 8543
Overall thickness ISO 1765
Pile service weight



Struttura

Tufted
approx. 400
Loop
Style
100% Econyl by Aquafil
PES
Conductive action back
approx. 2000 g/m²
approx. 7,0 - 8,0 mm
approx. 800 g/m²

Application

Wearability EN 1307 commercial use heavy (33)
Comfort class EN 1307 LC2

Ecological characteristics

Conformity certificate 1658-CPR-3032
DOP 1045-126868
EPD (Environmental Product Declaration) EPD-GUT-20160117-CCA1-EN

Fastness

Light fastness ISO 105-B02 ≥ 6
Water fastness EN ISO 105 E01 ≥ 5
Friction fastness EN ISO 105-X12 ≥ 5



Release Date 14.11.2022.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com