

## Characteristic features EN 1307



Name of article	<b>Struttura</b>	Secondary backing ISO 2424	Conductive action back
Method of production ISO 2424	Tufted	Electrostatic loading ISO 6356	< 2 KV
Width ISO 3018	ca. 400	Surface resistivity ISO 10965 ROT	10 <sup>9</sup> Ω
Surface structure ISO 2424	Loop	Transparency to heat ISO 8302	0,09 K*m <sup>2</sup> /W
Colourways	Style	Light fastness ISO 105-B02	≥ 6
Pile material ISO 2424	100% Econyl by Aquafil	Water fastness EN ISO 105 E01	≥ 5
Primary backing ISO 2424	PES	Friction fastness EN ISO 105-X12	≥ 5
Overall weight ISO 8543	ca. 2000 g/m <sup>2</sup>	Stitch rate ISO 1763	ca. 250.000/m <sup>2</sup>
Overall thickness ISO 1765	ca. 7,0 - 8,0 mm		
Pile service weight	ca. 800 g/m <sup>2</sup>		



EN 14041 | DOP: 1060 OC 3379 | NB: 1658

### Health-promoting properties AIR

- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers



### Health-promoting ACOUSTIC properties

- Improved impact sound insulation +25dB
- Enhanced room acoustics +0.25α<sub>w</sub>

Hz	125	250	500	1000	2000	4000
α <sub>s</sub>	0,	0,	0,	0,	0,	0,

- Increased employee concentration and motivation through enhanced well-being
- Acoustically effective



### Environmental properties

C9857DCD  
PRODIS-ID | product pass

- 100% recycled yarn
- Recycled primary backing
- Easy cleaning with water only



### Product Information

The smallest twisted yarn loops create a structured yet homogeneous texture. The delayed regeneration behavior of the tufting is typical of the fabric. Indentations in the fibers recover after a short period of frequent use.

### Installation Instructions

The seam is cut professionally from above within the nap alley using a seam cutter (e.g. from Mittag). During this work process, it must be ensured that the nap alley is not left during cutting.



Made in Europe (production according to EU standard)