

## Characteristic features EN 1307



Name of article	<b>Tosh 1400</b>	Secondary backing ISO 2424	Action back
Method of production ISO 2424	Tufted	Electrostatic loading ISO 6356	< 2 KV
Width ISO 3018	ca. 400	Surface resistivity ISO 10965 ROT	10 <sup>9</sup> Ω
Surface structure ISO 2424	Shag	Transparency to heat ISO 8302	0,09 K*m <sup>2</sup> /W
Colourways	Mix	Light fastness ISO 105-B02	≥ 5
Pile material ISO 2424	100% PA 6.6	Water fastness EN ISO 105 E01	≥ 4
Primary backing ISO 2424	PP	Friction fastness EN ISO 105-X12	≥ 3-4
Overall weight ISO 8543	ca. 2390 g/m <sup>2</sup>	Stitch rate ISO 1763	ca. 31.500/m <sup>2</sup>
Overall thickness ISO 1765	ca. 11,5 mm		
Pile service weight	ca. 1440 g/m <sup>2</sup>		



EN 14041 | DOP: 1060 OC 3547 | NB: 1658

### Health-promoting properties AIR



- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers

HEALTH



### Health-promoting ACOUSTIC properties



- Improved impact sound insulation +32dB
- Enhanced room acoustics +0.3α<sub>w</sub>

Hz	125	250	500	1000	2000	4000
α <sub>s</sub>	0,05	0,10	0,20	0,40	0,65	0,70

- Increased employee concentration and motivation through enhanced well-being
- Acoustically effective



### Environmental properties

F1BFCB9C  
PRODID | product pass

- Recycled primary backing
- Easy cleaning with water only



### Product Information

With its voluminous, extra high pile, the shag quality creates a wool-like, homogeneous appearance.

### Installation Instructions

An accurate, professional seam cut is made on the back of this shag quality, inside the nap, using a chopping knife. The use of "pile clamps" should be avoided; alternatively, it is recommended that the pile is carefully taped to the side with masking tape, which can be easily removed after insertion.



Made in Europe (production according to EU standard)

Data status 23.07.2024. Subject to changes due to technical advancements.