

## Characteristic features EN 1307

|                               |                 |                                   |                   |
|-------------------------------|-----------------|-----------------------------------|-------------------|
| Name of article               | <b>AT Tunis</b> | Secondary backing ISO 2424        | Welltex® Acoustic |
| Method of production ISO 2424 | Flat woven      | Electrostatic loading ISO 6356    | < 2 KV            |
| Width ISO 3018                | ca. 50x50       | Surface resistivity ISO 10965 ROT | 10 <sup>9</sup> Ω |
| Surface structure ISO 2424    | Loop            | Transparency to heat ISO 8302     | 0,09 K*m² /W      |
| Colourways                    | Style           | Light fastness ISO 105-B02        | ≥ 5               |
| Pile material ISO 2424        | 100% PET        | Water fastness EN ISO 105 E01     | ≥ 4               |
| Primary backing ISO 2424      | PET             | Friction fastness EN ISO 105-X12  | ≥ 3-4             |
| Overall weight ISO 8543       | ca. 3700 g/m²   | Stitch rate ISO 1763              | ca. 156.000/m²    |
| Overall thickness ISO 1765    | ca. 5,0 mm      |                                   |                   |
| Pile service weight           | ca. 655 g/m²    |                                   |                   |



EN 14041 | DOP: 1060-OC-6323-C4  
CPR: 0809-CPR-19006323-C4 | NB: 1658

### Health-promoting properties AIR

- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers

**HEALTH**

### Health-promoting ACOUSTIC properties

- High acoustic effectiveness as standard
- Improved impact sound insulation +20dB
- Enhanced room acoustics +0.2α<sub>w</sub>
- Increased employee concentration and motivation through enhanced well-being

| Hz             | 125  | 250  | 500  | 1000 | 2000 | 4000 |
|----------------|------|------|------|------|------|------|
| α <sub>s</sub> | 0,01 | 0,02 | 0,07 | 0,19 | 0,28 | 0,32 |

### Environmental properties

9C9535A2  
PRODUSID | product pass

- Completely recyclable
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- Easy cleaning with water only



### Product Information

### Installation Instructions



Made in Europe (production according to EU standard)

Data status 30.06.2025. Subject to changes due to technical advancements.