Characteristic features EN 1307

Name of article

Method of production ISO 2424

Width ISO 3018

Surface structure ISO 2424

Colourways

Pile material ISO 2424

Primary backing ISO 2424

Overall weight ISO 8543

Overall thickness ISO 1765

Pile service weight

AT Twist 600

Tufted

ca. 50x50

Loop

Mix

100% Econyl by Aquafil

PES

ca. 1900 g/m^2

ca. 5.8 mm

ca. 600 g/m^2

Secondary backing ISO 2424

Electrostatic loading ISO 6356

Surface resistivity ISO 10965 ROT

Transparency to heat ISO 8302

Light fastness ISO 105-B02 Water fastness EN ISO 105 E01

Friction fastness EN ISO 105-X12

Stitch rate ISO 1763

Welltex® Acoustic

< 2 KV

 $10^9 \Omega$

 $0.09 \, K^* m^2 / W$

> 5

> 4

> 3-4

ca. $154.800/m^2$

























EN 14041 | DOP: 1060-OC-3497 CPR: 1658-CPR-3497 | NB: 1658





- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers



70 710 3720-8





Health-promoting ACOUSTIC properties



- High acoustic effectiveness as standard
- Improved impact sound insulation +25dB Enhanced room acoustics $+0.25\alpha$
- 1000 125 250 500 2000 4000 0,05 0,25 0,25 0,00 0,25 0,35
- Increased employee concentration and motivation through enhanced well-being

Environmental properties

9239DFFB PRODIS-ID | product pass

- Completely recyclable
- 100% recycled yarn
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- · Easy cleaning with water only

Product Information

AT TWIST - This tile stands out with its mélange loop that creates a tiled appearance. Especially in lighter colors, the tile pattern becomes distinctly visible due to the shadow effects in the tile joints. During initial use, this appearance devolops significantly thanks to daily maintenance with a brush vacuum cleaner. Experience how the tiles gain individual beauty over time.

Installation Instructions















Made in Europe (production according to EU standard)

