


OBJECT CARPET

Typical characteristics

Name of article	 Velaa 700
Method of production ISO 2424	Tufted
Width ISO 3018	approx. 400
Surface structure ISO 2424	Loop
Colourways	Style
Pile material ISO 2424	100% Econyl by Aquafil
Primary backing ISO 2424	PES
Secondary backing ISO 2424	Conductive action back
Overall weight ISO 8543	approx. 2000 g/m ²
Overall thickness ISO 1765	approx. 5,5 - 6,5 mm
Pile service weight	approx. 570 g/m ²
Additional equipment	OC Protect

Application

Wearability EN 1307	commercial use heavy (33)
Comfort class EN 1307	LC2

Ecological characteristics

Conformity certificate	1658-CPR-3032
DOP	1045-124870
EPD (Environmental Product Declaration)	EPD-GUT-20160117-CCA1-EN

Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4



Release Date 11.3.2020.

OBJECT CARPET GmbH Rechbergstrasse 19 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com