#### Characteristic features EN 1307

Name of article

Method of production ISO 2424

Width ISO 3018

Surface structure ISO 2424

Colourways

Pile material ISO 2424

Primary backing ISO 2424

Overall weight ISO 8543

Overall thickness ISO 1765

Pile service weight

AT Walk x Talk

Flat woven

ca. 50x50

Loop

Mix

100% PA 6.6

**PES** 

ca.  $3500 \text{ g/m}^2$ 

ca. 5 mm

ca.  $415 \text{ g/m}^2$ 

Secondary backing ISO 2424

Electrostatic loading ISO 6356

Surface resistivity ISO 10965 ROT

Transparency to heat ISO 8302

Light fastness ISO 105-B02 Water fastness EN ISO 105 E01

Friction fastness EN ISO 105-X12

Stitch rate ISO 1763

Welltex® Acoustic

<2 KV

 $0.09 \, K^* m^2 / W$ 

≥ **5** 

≥ **4** > 3-4

ca.  $168000/m^2$ 



































EN 14041 | DOP: 1060-OC-6323-C3 CPR: 0809-CPR-19006323-C3 | NB: 1658

## **Health-promoting properties AIR**



- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers



# **Health-promoting ACOUSTIC properties**



- High acoustic effectiveness as standard
- Improved impact sound insulation +20dB Enhanced room acoustics  $+0.2\alpha$
- 1000 2000 Hz 125 250 500 4000 0,01 0,08 0,20 0,228 0,32
- Increased employee concentration and motivation through enhanced well-being

# 3B1CCDB7

**Environmental properties** 



- 100% recycled yarn
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- Easy cleaning with water only



### **Product Information**

Diese Teppichfliese besticht durch eine Web-Schlingenkonstruktion in meliertem Design, welche eine elegante Erscheinung mit sich bringt. Die Farbwahl spielt hierbei eine entscheidende Rolle für die Sichtbarkeit der Fliesen sowie den Pflegeaufwand. Bei helleren Farbtönen kann die Empfindlichkeit erhöht sein. Ein besonderes Kriterium ist das mögliche sichtbare Abzeichnen des Nahtbilds

### **Installation Instructions**

It is important to select the appropriate laying pattern (e.g., Chessboard) to achieve the desired visual effect.
















Data status 30.06.2025. Subject to changes due to technical advancements.