


OBJECT CARPET

Typical characteristics

Name of article	 Weave 700
Method of production ISO 2424	Flat woven
Width ISO 3018	approx. 400 cm
Surface structure ISO 2424	Loop
Colourways	Mix
Pile material ISO 2424	100% PA 6.6 Antron®
Primary backing ISO 2424	PA, PES
Secondary backing ISO 2424	Conductive action back
Overall weight ISO 8543	approx. 2200 g/m ²
Overall thickness ISO 1765	approx. 3,50 mm
Pile service weight	approx. 750 g/m ²

Application

Wearability EN 1307	commercial use heavy (33)
Comfort class EN 1307	LC1

Ecological characteristics

Conformity certificate	2531-CPR-CXA10145
DOP	1045-125067
EPD (Environmental Product Declaration)	EPD-OBJ-20160206-CAC1-EN

Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4



Release Date 1.7.2019.

OBJECT CARPET GmbH Rechbergstrasse 19 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com