OBJECT CARPET

Typical characteristics

Name of article	**Weave 700**
Method of production ISO 2424	Woven
Width ISO 3018	approx. 400
Surface structure ISO 2424	Flat woven
Colourways	Mix
Pile material ISO 2424	100% PA 6.6
Primary backing ISO 2424	PA, PES
Secondary backing ISO 2424	Action back
Overall weight ISO 8543	approx. 2200 g/m^2
Overall thickness ISO 1765	approx. 3,50 mm
Pile service weight	approx. 750 g/m^2

Application

Wearability EN 1307	commercial use heavy (33)
Comfort class EN 1307	LC1

Ecological characteristics

Conformity certificate	0809-CPR-19006323 - C2
DOP	1060-OC-6323-C2
EPD (Environmental Product Declaration)	EPD-OBJ-20220317-CBC1-EN
Prodis-ID	CAFA79F9

Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4

Release Date 6.11.2026.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com