

## Characteristic features EN 1307



Name of article	<b>AT Web Code 400</b>	Secondary backing ISO 2424	Welltex® Acoustic
Method of production ISO 2424	Flat woven	Electrostatic loading ISO 6356	< 2 KV
Width ISO 3018	ca. 50x50	Surface resistivity ISO 10965 ROT	10 <sup>9</sup> Ω
Surface structure ISO 2424	Loop	Transparency to heat ISO 8302	0,09 K*m <sup>2</sup> /W
Colourways	Mix	Light fastness ISO 105-B02	≥ 5
Pile material ISO 2424	100% PA 6.6	Water fastness EN ISO 105 E01	≥ 4
Primary backing ISO 2424	PES	Friction fastness EN ISO 105-X12	≥ 3-4
Overall weight ISO 8543	ca. 3000 g/m <sup>2</sup>	Stitch rate ISO 1763	ca. 156.000/m <sup>2</sup>
Overall thickness ISO 1765	ca. 5,0 mm		
Pile service weight	ca. 560 g/m <sup>2</sup>		



EN 14041 | DOP: 1060 OC 6323-C3 | NB: 1658

### Health-promoting properties AIR

- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers



### Health-promoting ACOUSTIC properties

- High acoustic effectiveness as standard
  - Improved impact sound insulation +20dB
  - Enhanced room acoustics +0.2α<sub>w</sub>
- |                |      |      |      |      |      |      |
|----------------|------|------|------|------|------|------|
| Hz             | 125  | 250  | 500  | 1000 | 2000 | 4000 |
| α <sub>s</sub> | 0,01 | 0,01 | 0,08 | 0,20 | 0,28 | 0,32 |
- Increased employee concentration and motivation through enhanced well-being



### Environmental properties

1EEACB9B  
PRODIS-ID | product pass

- Completely recyclable
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- Easy cleaning with water only



### Product Information

AT WEB CODE - This carpet tile captivates with a woven loop construction in a mottled design, bringing forth an elegant appearance. The choice of color plays a crucial role in the visibility of the tiles as well as the maintenance effort. Lighter shades may increase sensitivity. A particular criterion is the potential visibility of the seam pattern.

### Installation Instructions

It is important to select the appropriate laying pattern (e.g., Herringbone) to achieve the desired visual effect.



Made in Europe (production according to EU standard)