



| | | | |
|-------------------------------|--------------------|-----------------------------------|-------------------|
| Name of article | Web Pix 400 | Secondary backing ISO 2424 | Welltex® Acoustic |
| Method of production ISO 2424 | Flat woven | Electrostatic loading ISO 6356 | < 2 KV |
| Width ISO 3018 | ca. 400 | Surface resistivity ISO 10965 ROT | |
| Surface structure ISO 2424 | Loop | Transparency to heat ISO 8302 | 0,09 K*m² /W |
| Colourways | Mix | Light fastness ISO 105-B02 | ≥ 5 |
| Pile material ISO 2424 | 100% PA 6.6 | Water fastness EN ISO 105 E01 | ≥ 4 |
| Primary backing ISO 2424 | PES | Friction fastness EN ISO 105-X12 | ≥ 3-4 |
| Overall weight ISO 8543 | ca. 2300 g/m² | Stitch rate ISO 1763 | ca. 156.000/m² |
| Overall thickness ISO 1765 | ca. 4,50 mm | | |
| Pile service weight | ca. 560 g/m² | | |




EN 14041 | DOP: 1060-OC-6323-C2
CPR: 0809-CPR-19006323-C2 | NB: 1658

Health-promoting properties AIR



- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers

HEALTH



Health-promoting ACOUSTIC properties



- High acoustic effectiveness as standard
- Improved impact sound insulation +20dB
- Enhanced room acoustics +0.2α_w

| Hz | 125 | 250 | 500 | 1000 | 2000 | 4000 |
|----------------|------|------|------|------|------|------|
| α _s | 0,00 | 0,05 | 0,20 | 0,25 | 0,10 | 0,15 |

- Increased employee concentration and motivation through enhanced well-being



Environmental properties

BD435E3D
PRODUSID | product pass

- Completely recyclable
- Recycled primary backing
- 100% recycled secondary backing
- Easy cleaning with water only



Product Information

The finely mottled loop quality creates a pixelated, wool-like weave structure. Seam markings on small-patterned flatweaves are typical of the fabric. The reason for the occasional zipper effect in the appearance at the seam edges is not due to the design, but to the fabric construction or patterning.

Installation Instructions

The precise seam cut is carried out professionally using a steel ruler and a laying knife with a trapezoidal blade. The use of pile scissors is recommended for processing cut studs to ensure a flawless appearance.



Made in Europe (production according to EU standard)

Data status 30.06.2025. Subject to changes due to technical advancements.