

OBJECT CARPET

Typical characteristics

Name of article
Method of production ISO 2424
Width ISO 3018
Surface structure ISO 2424
Colourways
Pile material ISO 2424
Primary backing ISO 2424
Secondary backing ISO 2424
Overall weight ISO 8543
Overall thickness ISO 1765
Pile service weight
Additional equipment



Web Uni 400
Flat woven
approx. 400 cm
Loop
Mix
100% PA 6.6
PES
BlackThermo®Filz acoustic plus
approx. 2300 g/m²
approx. 4,50 mm
approx. 560 g/m²
OC Protect

Application

Wearability EN 1307 commercial use heavy (33)
Comfort class EN 1307 LC1

Ecological characteristics

Conformity certificate 2531-CPR-CXA10194
DOP 1045-122993
EPD (Environmental Product Declaration) EPD-OBJ-20160206-CAC1-EN

Fastness

Light fastness ISO 105-B02 ≥ 5
Water fastness EN ISO 105 E01 ≥ 4
Friction fastness EN ISO 105-X12 ≥ 3-4



Release Date 1.7.2019.

OBJECT CARPET GmbH Rechbergstrasse 19 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com